

Der projektbezogene Nullpunkt $\pm 0,00$ = OKFF liegt bei #Höhe
Der Bemessungswasserstand liegt bei ca. #####

The diagram illustrates a wall cross-section with various construction details and their corresponding symbols. The wall is shown in a cross-section view, with different materials and components labeled. The symbols are defined in a legend on the right.

Legend:


- zweischaliges MW gem. Statik, WSNW, SSN
- KS-MW gem. Statik
- Stahlbeton gem. Statik
- GKB / GKI - Vorsatzschalen
- GKB / GKI - Wand
- Detailverweis Horizontalschnitt
- Detailverweis Vertikalschnitt
- OKRD - 0,20 Oberkante Rohdecke
- OKFF ± 0,00 Oberkante Fertigfußboden
- UK RD Unterakte Rohdecke
- BRH Brüstungshöhe von OKFF
- Verlegerichtung Fliesen

Wall Cross-Section Details:

- BRANDSCHUTZ** (Fire Protection): Indicated by a red hatched pattern.
- tragende und aussteifende Bauteile mindestens F30** (Load-bearing and stiffening components at least F30): Indicated by a red hatched pattern.
- Wände F90-AB** (Walls F90-AB): Indicated by a red hatched pattern.
- Decken F90-AB** (Floors F90-AB): Indicated by a red hatched pattern.
- Wände F30** (Walls F30): Indicated by a yellow hatched pattern.
- Decken F30** (Floors F30): Indicated by a yellow hatched pattern.
- Rettungsweg** (Escape Route): Indicated by a green hatched pattern.
- anlieferbare Stelle** (Deliverable location): Indicated by a blue hatched pattern.
- Bedienstelle Öffnung Dachfenster** (Control point for roof window opening): Indicated by a blue hatched pattern.
- Rauchabzugsfenster freier Querschnitt >0,5m²** (Smoke extraction window with free cross-section >0.5m²): Indicated by a blue hatched pattern.
- Rauchschutztür T30** (Smoke protection door T30): Indicated by a blue hatched pattern.
- Tür, dichtschiessend** (Door, tight-closing): Indicated by a blue hatched pattern.

[illegible]

VORABZUG



Von-Vincke-Straße

Südost SA ▼

t SA ▲